


FUNCTION SET-UP MODE—HELI



SPEKTRUM

Leaders in Spread Spectrum Technology

			AILE	ELEV	RUDD
DUAL RATE	0	D/R	100 %	100 %	100 %
		EXP	20 %	20 %	30 %
EXPO	1	D/R	100 %	100 %	100 %
		EXP	20 %	20 %	30 %

	THRO	AILE	ELEV	RUDD	GEAR	PITCH	AUX2
REVERSE SW	R • N	R • N	R • N	R • N	R • N	R • N	R • N
SUB TRIM	AS NEEDED						
TRAVEL ADJUST	H %04	L %15	U %15	L %10	+ %100	H %15	H %100

	AILE	ELEV	PITCH	EXPO
SWASH MIX	+100 %	+100 %	-42 %	ON
	REV R • N	REV R • N	REV R • N	OFF

THROTTLE HOLD	INHIBIT	POSITION	SWITCH
	ACTIVE	0.0 %	D/R

THROTTLE CURVE		P-LOW	P-1	P-MID	P-3	P-HIGH	EXPO
	NORMAL	0	INH	86	INH	100	ACT
	STUNT 1	100	INH	92	INH	100	ACT
	STUNT 2	100	INH	100	INH	100	ACT

PITCH CURVE		P-LOW	P-1	P-MID	P-3	P-HIGH	EXPO
	NORMAL	0	INH	50	INH	100	INH
	STUNT 1	0	INH	50	INH	100	INH
	STUNT 2	0	INH	50	INH	100	INH
	HOLD	0	INH	50	INH	100	INH

REVO MIX	NORMAL	UP	0 %
		DOWN	0 %
	STUNT	UP	0 %
		DOWN	0 %

		MANUAL	AUTOMATIC
GYRO SENS	0	100	
	1	100	

		CHANNEL	SW	+POS	-POS	OFFSET	SWITCH
PROGRAM MIX	MIX 1	AILE - THRO	S 12	+30 %	-30 %	0	S 12
	MIX 2	ELEV - THRO	S 12	+30 %	-30 %	0	S 12
	MIX 3	-		%	%		

TIMER	STOP WATCH	
	COUNTDOWN	7:00

